

# Greenleaf Nozzles for Golf Course and Turf Grass Applications

Greenleaf nozzles are designed to provide a unique balance of coverage, penetration and drift control. The single fan TurboDrop® TDXL is preferred for soil applied products and for maximum drift control. The DualFan TDAD provides “two-sided” coverage for growth regulators, contact fungicides and other coverage critical applications. Both deliver air-energized spray droplets for maximizing on-target performance, and both nozzles come apart by hand for easy maintenance. They are available in a variety of sizes, with either a poly (TDXL, TDAD) or ceramic metering orifice (TDCXL, TDCAD).

\*Also available in ceramic metering orifice.

Add "C" after TD for Ceramic.

## GALLONS PER 1000 SQFT BASED ON 20" NOZZLE SPACING

	TDXL Droplet	DualFan Droplet	PSI	GPM	2 MPH	2.5 MPH	3 MPH	3.5 MPH	4 MPH	4.5 MPH	5 MPH	5.5 MPH	6 MPH	
Standard TurboDrop (Use 100 mesh)	TDXL110015*	C	M	30	0.13	0.44	0.35	0.29	0.25	0.22	0.20	0.18	0.16	0.15
		C	M	40	0.15	0.51	0.41	0.34	0.29	0.26	0.23	0.20	0.19	0.17
		M	M	50	0.17	0.57	0.46	0.38	0.33	0.29	0.25	0.23	0.21	0.19
		M	M	60	0.18	0.62	0.50	0.42	0.36	0.31	0.28	0.25	0.23	0.21
		M	M	70	0.20	0.67	0.54	0.45	0.39	0.34	0.30	0.27	0.25	0.22
	TDAD15*	F	F	80	0.21	0.72	0.58	0.48	0.41	0.36	0.32	0.29	0.26	0.24
		F	F	100	0.24	0.81	0.65	0.54	0.46	0.40	0.36	0.32	0.29	0.27
	TDXL11002*	C	C	30	0.17	0.59	0.47	0.39	0.34	0.29	0.26	0.24	0.21	0.20
		C	M	40	0.20	0.68	0.54	0.45	0.39	0.34	0.30	0.27	0.25	0.23
		M	M	50	0.22	0.76	0.61	0.51	0.43	0.38	0.34	0.30	0.28	0.25
		M	M	60	0.24	0.83	0.67	0.56	0.48	0.42	0.37	0.33	0.30	0.28
		M	M	70	0.26	0.90	0.72	0.60	0.51	0.45	0.40	0.36	0.33	0.30
DualFan TurboDrop (Use 100 mesh)	TDAD02*	F	F	80	0.28	0.96	0.77	0.64	0.55	0.48	0.43	0.38	0.35	0.32
		F	F	100	0.32	1.08	0.86	0.72	0.61	0.54	0.48	0.43	0.39	0.36
	TDXL110025*	VC	C	30	0.22	0.74	0.59	0.49	0.42	0.37	0.33	0.29	0.27	0.25
		VC	C	40	0.25	0.85	0.68	0.57	0.49	0.43	0.38	0.34	0.31	0.28
		C	M	50	0.28	0.95	0.76	0.63	0.54	0.48	0.42	0.38	0.35	0.32
		M	M	60	0.31	1.04	0.83	0.69	0.59	0.52	0.46	0.42	0.38	0.35
		M	M	70	0.33	1.12	0.90	0.75	0.64	0.56	0.50	0.45	0.41	0.37
	TDAD025*	M	M	80	0.35	1.20	0.96	0.80	0.69	0.60	0.53	0.48	0.44	0.40
		M	F	100	0.40	1.34	1.08	0.90	0.77	0.67	0.60	0.54	0.49	0.45
Standard TurboDrop (Use 50 mesh)	TDXL11003*	XC	C	30	0.26	0.88	0.71	0.59	0.50	0.44	0.39	0.35	0.32	0.29
		VC	C	40	0.30	1.02	0.82	0.68	0.58	0.51	0.45	0.41	0.37	0.34
		C	M	50	0.34	1.14	0.91	0.76	0.65	0.57	0.51	0.46	0.41	0.38
		C	M	60	0.37	1.25	1.00	0.83	0.71	0.62	0.56	0.50	0.45	0.42
		M	M	70	0.40	1.35	1.08	0.90	0.77	0.67	0.60	0.54	0.49	0.45
	TDAD03*	M	M	80	0.42	1.44	1.15	0.96	0.82	0.72	0.64	0.58	0.52	0.48
		M	F	100	0.47	1.61	1.29	1.08	0.92	0.81	0.72	0.65	0.59	0.54
DualFan TurboDrop (Use 50 mesh)	TDAD04*	XC	C	30	0.35	1.18	0.94	0.79	0.67	0.59	0.52	0.47	0.43	0.39
		VC	C	40	0.40	1.36	1.09	0.91	0.78	0.68	0.60	0.54	0.49	0.45
		C	M	50	0.45	1.52	1.22	1.01	0.87	0.76	0.68	0.61	0.55	0.51
		C	M	60	0.49	1.67	1.33	1.11	0.95	0.83	0.74	0.67	0.61	0.56
		M	M	70	0.53	1.80	1.44	1.20	1.03	0.90	0.80	0.72	0.65	0.60
	TDAD05*	M	M	80	0.57	1.92	1.54	1.28	1.10	0.96	0.85	0.77	0.70	0.64
		M	F	100	0.63	2.15	1.72	1.43	1.23	1.08	0.96	0.86	0.78	0.72
Standard TurboDrop (Use 24 mesh)	TDXL11005*	XC	VC	30	0.43	1.47	1.18	0.98	0.84	0.74	0.65	0.59	0.54	0.49
		XC	C	40	0.50	1.70	1.36	1.13	0.97	0.85	0.76	0.68	0.62	0.57
		VC	C	50	0.56	1.90	1.52	1.27	1.09	0.95	0.84	0.76	0.69	0.63
		VC	M	60	0.61	2.08	1.67	1.39	1.19	1.04	0.93	0.83	0.76	0.69
		C	M	70	0.66	2.25	1.80	1.50	1.29	1.12	1.00	0.90	0.82	0.75
	TDAD05*	C	M	80	0.71	2.40	1.92	1.60	1.37	1.20	1.07	0.96	0.87	0.80
		C	M	100	0.79	2.69	2.15	1.79	1.54	1.34	1.19	1.08	0.98	0.90
DualFan TurboDrop (Use 50 mesh)	TDXL11006*	XC	VC	30	0.52	1.77	1.41	1.18	1.01	0.88	0.79	0.71	0.64	0.59
		XC	VC	40	0.60	2.04	1.63	1.36	1.17	1.02	0.91	0.82	0.74	0.68
		XC	C	50	0.67	2.28	1.82	1.52	1.30	1.14	1.01	0.91	0.83	0.76
		VC	C	60	0.73	2.50	2.00	1.67	1.43	1.25	1.11	1.00	0.91	0.83
		VC	M	70	0.79	2.70	2.16	1.80	1.54	1.35	1.20	1.08	0.98	0.90
	TDAD06*	C	M	80	0.85	2.88	2.31	1.92	1.65	1.44	1.28	1.15	1.05	0.96
		C	M	100	0.95	3.23	2.58	2.15	1.84	1.61	1.43	1.29	1.17	1.08
Standard TurboDrop (Use 24 mesh)	TDXL11008*	XC	VC	30	0.69	2.36	1.88	1.57	1.35	1.18	1.05	0.94	0.86	0.79
		XC	VC	40	0.80	2.72	2.18	1.81	1.55	1.36	1.21	1.09	0.99	0.91
		XC	C	50	0.89	3.04	2.43	2.03	1.74	1.52	1.35	1.22	1.11	1.01
		XC	C	60	0.98	3.33	2.67	2.22	1.90	1.67	1.48	1.33	1.21	1.11
	TDAD08*	VC	C	70	1.06	3.60	2.88	2.40	2.06	1.80	1.60	1.44	1.31	1.20
		VC	M	80	1.13	3.85	3.08	2.56	2.20	1.92	1.71	1.54	1.40	1.28
		C	M	100	1.26	4.30	3.44	2.87	2.46	2.15	1.91	1.72	1.56	1.43
DualFan TurboDrop (Use 24 mesh)	TDXL11010*	XC	VC	30	0.87	2.94	2.36	1.96	1.68	1.47	1.31	1.18	1.07	0.98
		XC	C	40	1.00	3.40	2.72	2.27	1.94	1.70	1.51	1.36	1.24	1.13
		XC	VC	50	1.12	3.80	3.04	2.53	2.17	1.90	1.69	1.52	1.38	1.27
		XC	C	60	1.22	4.16	3.33	2.78	2.38	2.08	1.85	1.67	1.51	1.39
	TDAD10*	C	M	70	1.32	4.50	3.60	3.00	2.57	2.25	2.00	1.80	1.64	1.50
		VC	C	80	1.41	4.81	3.85	3.21	2.75	2.40	2.14	1.92	1.75	1.60
		VC	M	100	1.58	5.38	4.30	3.58	3.07	2.69	2.39	2.15	1.95	1.79
Standard TurboDrop (Use 24 mesh)	AMDF12	VC	C	30	1.04	3.53	2.83	2.36	2.02	1.77	1.57	1.41	1.28	1.18
		C	C	40	1.20	4.08	3.26	2.72	2.33	2.04	1.81	1.63	1.48	1.36
		C	C	50	1.34	4.56	3.65	3.04	2.61	2.28	2.03	1.82	1.66	1.52
		C	C	60	1.47	5.00	4.00	3.33	2.86	2.50	2.22	2.00	1.82	1.67
	TDAD10*	M	M	70	1.59	5.40	4.32	3.60	3.08	2.70	2.40	2.16	1.96	1.80
		M	M	80	1.70	5.77	4.62	3.85	3.30	2.88	2.56	2.31	2.10	1.92
		M	M	90	1.80	6.12	4.90	4.08	3.50	3.06	2.72	2.45	2.23	2.04
DualFan TurboDrop (Use 24 mesh)	TDXL11015*	30	1.30	4.42	3.53	2.94	2.52	2.21	1.96	1.77	1.61	1.47		
		40	1.50	5.10	4.08	3.40	2.91	2.55	2.27	2.04	1.85	1.70		
		50	1.68	5.70	4.56	3.80	3.26	2.85	2.53	2.28	2.07	1.90		
		60	1.84	6.25	5.00	4.16	3.57	3.12	2.78	2.50	2.27	2.08		
	TDAD15*	70	1.98	6.75	5.40	4.50	3.86	3.37	3.00	2.70	2.45	2.25		
		80	2.12	7.21	5.77	4.81	4.12	3.61	3.21	2.88	2.62	2.40		
		90	2.37	8.06	6.45	5.38	4.61	4.03	3.58	3.23	2.93	2.69		

Droplet size classifications are rated on ASABE 572.1