AirMix DualFan Nozzles - 20” Spacing Tabulation Chart (Page 1)

The AirMix® Dual Fan Nozzle can be used in a variety of applications from burndown with glyphosate to insecticides, fungicides and other contact chemicals. The dual 110° fans are oriented 10° forward and 50° rearward to provide a combination of penetration and backside coverage in complex canopies. To maximize coverage, the nozzles may be alternated on the boom to provide four angles of spray orientation into the canopy, effectively spraying the target four times in one pass.

Pressure Range: 15-90 psi **Recommended Boom Height:** 15-25”
Materials of Construction: Polyacetal, EPDM

AirMix DualFan

AMDF02
AMDF025
AMDF03
AMDF035
AMDF04
AMDF045
AMDF05
AMDF055
AMDF06
AMDF07
AMDF08
AMDF09
AMDF10
AMDF11
AMDF12

					GALLONS PER ACRE BASED ON 20" NOZZLE SPACING																
	Droplet	Drift %	PSI	GPM	4 MPH	5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	11 MPH	12 MPH	13 MPH	14 MPH	15 MPH	16 MPH	17 MPH	18 MPH	19 MPH	20 MPH
AMDF02	XC	0.4	15	0.12	9.1	7.3	6.1	5.2	4.5	4.0	3.6	3.3	3.0	2.8	2.6	2.4	2.3	2.1	2.0	1.9	1.8
	VC	0.9	20	0.14	10.5	8.4	7.0	6.0	5.3	4.7	4.2	3.8	3.5	3.2	3.0	2.8	2.6	2.5	2.3	2.2	2.1
	C	1.9	30	0.17	12.9	10.3	8.6	7.3	6.4	5.7	5.1	4.7	4.3	4.0	3.7	3.4	3.2	3.0	2.9	2.7	2.6
	M	3.5	40	0.20	14.9	11.9	9.9	8.5	7.4	6.6	5.9	5.4	5.0	4.6	4.2	4.0	3.7	3.5	3.3	3.1	3.0
	M	5.2	50	0.22	16.6	13.3	11.1	9.5	8.3	7.4	6.6	6.0	5.5	5.1	4.7	4.4	4.2	3.9	3.7	3.5	3.3
	M	6.7	60	0.24	18.2	14.5	12.1	10.4	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6
	M	7.8	70	0.26	19.6	15.7	13.1	11.2	9.8	8.7	7.9	7.1	6.5	6.0	5.6	5.2	4.9	4.6	4.4	4.1	3.9
	M	9.2	80	0.28	21.0	16.8	14.0	12.0	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2
	M	10.8	90	0.30	22.3	17.8	14.9	12.7	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5
AMDF025	XC	0.6	15	0.15	11.4	9.1	7.6	6.5	5.7	5.1	4.5	4.1	3.8	3.5	3.2	3.0	2.8	2.7	2.5	2.4	2.3
	VC	1.1	20	0.18	13.1	10.5	8.8	7.5	6.6	5.8	5.3	4.8	4.4	4.0	3.8	3.5	3.3	3.1	2.9	2.8	2.6
	VC	2.2	30	0.22	16.1	12.9	10.7	9.2	8.0	7.1	6.4	5.8	5.4	4.9	4.6	4.3	4.0	3.8	3.6	3.4	3.2
	C	3.7	40	0.25	18.6	14.9	12.4	10.6	9.3	8.3	7.4	6.8	6.2	5.7	5.3	5.0	4.6	4.4	4.1	3.9	3.7
	M	5.4	50	0.28	20.8	16.6	13.8	11.9	10.4	9.2	8.3	7.5	6.9	6.4	5.9	5.5	5.2	4.9	4.6	4.4	4.2
	M	6.8	60	0.31	22.7	18.2	15.2	13.0	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5
	M	8.2	70	0.33	24.6	19.6	16.4	14.0	12.3	10.9	9.8	8.9	8.2	7.6	7.0	6.5	6.1	5.8	5.5	5.2	4.9
	M	9.5	80	0.35	26.3	21.0	17.5	15.0	13.1	11.7	10.5	9.5	8.8	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.3
	M	11.1	90	0.38	27.8	22.3	18.6	15.9	13.9	12.4	11.1	10.1	9.3	8.6	8.0	7.4	7.0	6.6	6.2	5.9	5.6
AMDF03	XC	0.7	15	0.18	13.6	10.9	9.1	7.8	6.8	6.1	5.5	5.0	4.5	4.2	3.9	3.6	3.4	3.2	3.0	2.9	2.7
	VC	1.2	20	0.21	15.8	12.6	10.5	9.0	7.9	7.0	6.3	5.7	5.3	4.8	4.5	4.2	3.9	3.7	3.5	3.3	3.2
	VC	2.4	30	0.26	19.3	15.4	12.9	11.0	9.6	8.6	7.7	7.0	6.4	5.9	5.5	5.1	4.8	4.5	4.3	4.1	3.9
	C	3.9	40	0.30	22.3	17.8	14.9	12.7	11.1	9.9	8.9	8.1	7.4	6.9	6.4	5.9	5.6	5.2	5.0	4.7	4.5
	M	5.5	50	0.34	24.9	19.9	16.6	14.2	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.6	6.2	5.9	5.5	5.2	5.0
	M	7.0	60	0.37	27.3	21.8	18.2	15.6	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5
	M	8.4	70	0.40	29.5	23.6	19.6	16.8	14.7	13.1	11.8	10.7	9.8	9.1	8.4	7.9	7.4	6.9	6.5	6.2	5.9
	M	9.8	80	0.42	31.5	25.2	21.0	18.0	15.8	14.0	12.6	11.5	10.5	9.7	9.0	8.4	7.9	7.4	7.0	6.6	6.3
	M	11.2	90	0.45	33.4	26.7	22.3	19.1	16.7	14.9	13.4	12.2	11.1	10.3	9.5	8.9	8.4	7.9	7.4	7.0	6.7
AMDF035	XC	0.6	15	0.21	15.9	12.7	10.6	9.1	8.0	7.1	6.4	5.8	5.3	4.9	4.5	4.2	4.0	3.7	3.5	3.4	3.2
	VC	1.1	20	0.25	18.4	14.7	12.3	10.5	9.2	8.2	7.4	6.7	6.1	5.7	5.3	4.9	4.6	4.3	4.1	3.9	3.7
	VC	2.2	30	0.30	22.5	18.0	15.0	12.9	11.3	10.0	9.0	8.2	7.5	6.9	6.4	6.0	5.6	5.3	5.0	4.7	4.5
	C	3.7	40	0.35	26.0	20.8	17.3	14.9	13.0	11.6	10.4	9.5	8.7	8.0	7.4	6.9	6.5	6.1	5.8	5.5	5.2
	M	5.3	50	0.39	29.1	23.2	19.4	16.6	14.5	12.9	11.6	10.6	9.7	8.9	8.3	7.7	7.3	6.8	6.5	6.1	5.8
	M	6.8	60	0.43	31.8	25.5	21.2	18.2	15.9	14.1	12.7	11.6	10.6	9.8	9.1	8.5	8.0	7.5	7.1	6.7	6.4
	M	8.3	70	0.46	34.4	27.5	22.9	19.6	17.2	15.3	13.8	12.5	11.5	10.6	9.8	9.2	8.6	8.1	7.6	7.2	6.9
	M	9.7	80	0.49	36.8	29.4	24.5	21.0	18.4	16.3	14.7	13.4	12.3	11.3	10.5	9.8	9.2	8.6	8.2	7.7	7.4
	M	11.1	90	0.53	39.0	31.2	26.0	22.3	19.5	17.3	15.6	14.2	13.0	12.0	11.1	10.4	9.7	9.2	8.7	8.2	7.8
AMDF04	XC	0.5	15	0.24	18.2	14.5	12.1	10.4	9.1	8.1	7.3	6.6	6.1	5.6	5.2	4.8	4.5	4.3	4.0	3.8	3.6
	VC	1.0	20	0.28	21.0	16.8	14.0	12.0	10.5	9.3	8.4	7.6	7.0	6.5	6.0	5.6	5.3	4.9	4.7	4.4	4.2
	VC	2.1	30	0.35	25.7	20.6	17.1	14.7	12.9	11.4	10.3	9.4	8.6	7.9	7.3	6.9	6.4	6.1	5.7	5.4	5.1
	C	3.5	40	0.40	29.7	23.8	19.8	17.0	14.9	13.2	11.9	10.8	9.9	9.1	8.5	7.9	7.4	7.0	6.6	6.3	5.9
	M	5.1	50	0.45	33.2	26.6	22.1	19.0	16.6	14.8	13.3	12.1	11.1	10.2	9.5	8.9	8.3	7.8	7.4	7.0	6.6
	M	6.7	60	0.49	36.4	29.1	24.2	20.8	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3
	M	8.2	70	0.53	39.3	31.4	26.2	22.5	19.6	17.5	15.7	14.3	13.1	12.1	11.2	10.5	9.8	9.2	8.7	8.3	7.9
	M	9.6	80	0.57	42.0	33.6	28.0	24.0	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4
	M	11.0	90	0.60	44.6	35.6	29.7	25.5	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9
AMDF045	XC	0.4	15	0.28	20.5	16.4	13.6	11.7	10.2	9.1	8.2	7.4	6.8	6.3	5.8	5.5	5.1	4.8	4.5	4.3	4.1
	VC	0.9	20	0.32	23.6	18.9	15.8	13.5	11.8	10.5	9.5	8.6	7.9	7.3	6.8	6.3	5.9	5.6	5.3	5.0	4.7
	VC	1.8	30	0.39	28.9	23.1	19.3	16.5	14.5	12.9	11.6	10.5	9.6	8.9	8.3	7.7	7.2	6.8	6.4	6.1	5.8
	C	3.0	40	0.45	33.4	26.7	22.3	19.1	16.7	14.9	13.4	12.2	11.1	10.3	9.5	8.9	8.4	7.9	7.4	7.0	6.7
	C	4.3	50	0.50	37.4	29.9	24.9	21.3	18.7	16.6	14.9	13.6	12.5	11.5	10.7	10.0	9.3	8.8	8.3	7.9	7.5
	C	5.6	60	0.55	40.9	32.7	27.3	23.4	20.5	18.2	16.4	14.9	13.6	12.6	11.7	10.9	10.2	9.6	9.1	8.6	8.2
	M	7.0	70	0.60	44.2	35.4	29.5	25.3	22.1	19.6	17.7	16.1	14.7	13.6	12.6	11.8	11.1	10.4	9.8	9.3	8.8
	M	8.2	80	0.64	47.3	37.8	31.5	27.0	23.6	21.0	18.9	17.2	15.8	14.5	13.5	12.6	11.8	11.1	10.5	9.9	9.5
	M	9.5	90	0.68	50.1	40.1	33.4	28.6	25.1	22.3	20.0	18.2	16.7	15.4	14.3	13.4	12.5	11.8	11.1	10.6	10.0
AMDF05	XC	0.4	15	0.31	22.7	18.2	15.2	13.0	11.4	10.1	9.1	8.3	7.6	7.0	6.5	6.1	5.7	5.3	5.1	4.8	4.5
	VC	0.8	20	0.35	26.3	21.0	17.5	15.0	13.1	11.7	10.5	9.5	8.8	8.1	7.5	7.0	6.6	6.2	5.8	5.5	5.3
	VC	1.5	30	0.43	32.2	25.7	21.4	18.4	16.1	14.3	12.9	11.7	10.7	9.9	9.2	8.6	8.0	7.6	7.1	6.8	6.4
	C	2.6	40	0.50	37.1	29.7	24.8	21.2	18.6	16.5	14.9	13.5	12.4	11.4	10.6	9.9	9.3	8.7	8.3	7.8	7.4
	C	3.6	50	0.56	41.5	33.2	27.7	23.7	20.8	18.4	16.6	15.1	13.8	12.8	11.9	11.1	10.4	9.8	9.2	8.7	8.3
	C	4.7	60	0.61	45.5	36.4	30.3	26.0	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1
	M	5.9	70	0.66	49.1	39.3	32.7	28.1	24.6	21.8	19.6	17.9	16.4	15.1	14.0	13.1	12.3	11.6	10.9	10.3	9.8
	M	7.1	80	0.71	52.5	42.0	35.0	30.0	26.3	23.3	21.0	19.1	17.5	16.2	15.0	14.0	13.1	12.4	11.7	11.1	10.5
	M	8.2	90	0.75	55.7	44.6	37.1	31.8	27.8	24.8	22.3	20.3	18.6	17.1	15.9	14.9	13.9	13.1	12.4	11.7	11.1
AMDF055	XC	0.4	15	0.34	25.0	20.0	16.7	14.3	12.5	11.1	10.0	9.1	8.3	7.7	7.1	6.7	6.3	5.9	5.6	5.3	5.0
	VC	0.8	20	0.39	28.9	23.1	19.3	16.5	14.4	12.8	11.6	10.5	9.6	8.9	8.3	7.7	7.2	6.8	6.4	6.1	5.8
	VC	1.4	30	0.48	35.4	28.3	23.6	20.2	17.7	15.7	14.1	12.9	11.8	10.9	10.1	9.4	8.8	8.3	7.9	7.4	7.1
	VC	2.4	40	0.55	40.8	32.7	27.2	23.3	20.4	18.2	16.3	14.9	13.6	12.6	11.7	10.9	10.2	9.6	9.1	8.6	8.2
	C	3.4	50	0.61	45.7	36.5	30.4	26.1	22.8	20.3	18.3	16.6	15.2	14.0	13.0	12.2	11.4	10.7	10.1	9.6	9.1
	C	4.4	60	0.67	50.0	40.0	33.3	28.6	25.0	22.2	20.0	18.2	16.7	15.4	14.3	13.3	12.5	11.8	11.1	10.5	10.0
	C	5.5	70	0.73	54.0	43.2	36.0	30.9	27.0	24.0	21.6	19.6	18.0	16.6	15.4	14.4	13.5	12.7	12.0	11.4	10.8
	M	6.6	80	0.78	57.8	46.2	38.5	33.0	28.9	25.7	23.1	21.0	19.3	17.8	16.5	15.4	14.4	13.6	12.8	12.2	11.6
	M	7.6	90	0.83	61.3	49.0	40.8	35.0	30.6	27.2	24.5	22.3	20.4	18.8	17.5	16.3	15.3	14.4	13.6	12.9	12.3
AMDF06	XC	0.4	15	0.37	27.3	21.8	18.2	15.6	13.6	12.1	10.9	9.9	9.1	8.4	7.8	7.3	6.8	6.4	6.1	5.7	5.5
	XC	0.8	20	0.42	31.5	25.2	21.0	18.0	15.8	14.0	12.6	11.5	10.5	9.7	9.0	8.4	7.9	7.4	7.0	6.6	6.3
	VC	1.4	30	0.52	38.6	30.9	25.7	22.0	19.3	17.1	15.4	14.0	12.9	11.9	11.0	10.3	9.6	9.1	8.6	8.1	7.7
	VC	2.3	40	0.60	44.6	35.6	29.7	25.5	22.3	19.8	17.8	16.2	14.9	13.7	12.7	11.9	11.1	10.5	9.9	9.4	8.9
	C	3.2	50	0.67	49.8	39.8	33.2	28.5	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	11.7	11.1	10.5	10.0
	C	4.2	60	0.73	54.6	43.6	36.4	31.2	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9
	C	5.3	70	0.79	58.9	47.1	39.3	33.7	29.5	26.2	23.6	21.4	19.6	18.1	16.8	15.7	14.7	13.9	13.1	12.4	11.8
	M	6.2	80	0.85	63.0	50.4	42.0	36.0	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.8	14.8	14.0	13.3	12.6
	M	7.0	90	0.90	66.8	53.5	44.6	38.2	33.4	29.7	26.7	24.3	22.3	20.6	19.1	17.8	16.7	15.7	14.9	14.1	13.4

Droplet data based off of ASABE S572.3 testing and Drift % is percent of <141um driftable fines.

AirMix DualFan Nozzles - 20” Spacing Tabulation Chart (Page 2)

The AirMix® Dual Fan Nozzle can be used in a variety of applications from burndown with glyphosate to insecticides, fungicides and other contact chemicals. The dual 110° fans are oriented 10° forward and 50° rearward to provide a combination of penetration and backside coverage in complex canopies. To maximize coverage, the nozzles may be alternated on the boom to provide four angles of spray orientation into the canopy, effectively spraying the target four times in one pass.

Pressure Range: 15-90 psi **Recommended Boom Height:** 15-25”
Materials of Construction: Polyacetal, EPDM

AirMix DualFan

AMDF02
AMDF025
AMDF03
AMDF035
AMDF04
AMDF045
AMDF05
AMDF055
AMDF06
AMDF07
AMDF08
AMDF09
AMDF10
AMDF11
AMDF12

					GALLONS PER ACRE BASED ON 20" NOZZLE SPACING																
	Droplet	Drift %	PSI	GPM	4 MPH	5 MPH	6 MPH	7 MPH	8 MPH	9 MPH	10 MPH	11 MPH	12 MPH	13 MPH	14 MPH	15 MPH	16 MPH	17 MPH	18 MPH	19 MPH	20 MPH
AMDF07	XC	0.4	15	0.43	31.8	25.5	21.2	18.2	15.9	14.1	12.7	11.6	10.6	9.8	9.1	8.5	8.0	7.5	7.1	6.7	6.4
	XC	0.7	20	0.49	36.8	29.4	24.5	21.0	18.4	16.3	14.7	13.4	12.3	11.3	10.5	9.8	9.2	8.6	8.2	7.7	7.4
	VC	1.3	30	0.61	45.0	36.0	30.0	25.7	22.5	20.0	18.0	16.4	15.0	13.8	12.9	12.0	11.3	10.6	10.0	9.5	9.0
	VC	2.2	40	0.70	52.0	41.6	34.7	29.7	26.0	23.1	20.8	18.9	17.3	16.0	14.9	13.9	13.0	12.2	11.6	10.9	10.4
	C	3.1	50	0.78	58.1	46.5	38.7	33.2	29.1	25.8	23.2	21.1	19.4	17.9	16.6	15.5	14.5	13.7	12.9	12.2	11.6
	C	4.1	60	0.86	63.7	50.9	42.4	36.4	31.8	28.3	25.5	23.1	21.2	19.6	18.2	17.0	15.9	15.0	14.1	13.4	12.7
	C	5.2	70	0.93	68.8	55.0	45.8	39.3	34.4	30.6	27.5	25.0	22.9	21.2	19.6	18.3	17.2	16.2	15.3	14.5	13.8
	M	6.2	80	0.99	73.5	58.8	49.0	42.0	36.8	32.7	29.4	26.7	24.5	22.6	21.0	19.6	18.4	17.3	16.3	15.5	14.7
	M	7.2	90	1.05	78.0	62.4	52.0	44.6	39.0	34.7	31.2	28.4	26.0	24.0	22.3	20.8	19.5	18.3	17.3	16.4	15.6
AMDF08	XC	0.4	15	0.49	36.4	29.1	24.2	20.8	18.2	16.2	14.5	13.2	12.1	11.2	10.4	9.7	9.1	8.6	8.1	7.7	7.3
	XC	0.7	20	0.57	42.0	33.6	28.0	24.0	21.0	18.7	16.8	15.3	14.0	12.9	12.0	11.2	10.5	9.9	9.3	8.8	8.4
	VC	1.3	30	0.69	51.4	41.2	34.3	29.4	25.7	22.9	20.6	18.7	17.1	15.8	14.7	13.7	12.9	12.1	11.4	10.8	10.3
	VC	2.2	40	0.80	59.4	47.5	39.6	33.9	29.7	26.4	23.8	21.6	19.8	18.3	17.0	15.8	14.9	14.0	13.2	12.5	11.9
	VC	3.1	50	0.89	66.4	53.1	44.3	37.9	33.2	29.5	26.6	24.1	22.1	20.4	19.0	17.7	16.6	15.6	14.8	14.0	13.3
	C	4.0	60	0.98	72.7	58.2	48.5	41.6	36.4	32.3	29.1	26.5	24.2	22.4	20.8	19.4	18.2	17.1	16.2	15.3	14.5
	C	5.1	70	1.06	78.6	62.9	52.4	44.9	39.3	34.9	31.4	28.6	26.2	24.2	22.5	21.0	19.6	18.5	17.5	16.5	15.7
	M	6.2	80	1.13	84.0	67.2	56.0	48.0	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	19.8	18.7	17.7	16.8
	M	7.2	90	1.20	89.1	71.3	59.4	50.9	44.6	39.6	35.6	32.4	29.7	27.4	25.5	23.8	22.3	21.0	19.8	18.8	17.8
AMDF09	XC	0.3	15	0.55	40.9	32.7	27.3	23.4	20.5	18.2	16.4	14.9	13.6	12.6	11.7	10.9	10.2	9.6	9.1	8.6	8.2
	XC	0.6	20	0.64	47.3	37.8	31.5	27.0	23.6	21.0	18.9	17.2	15.8	14.5	13.5	12.6	11.8	11.1	10.5	9.9	9.5
	VC	1.2	30	0.78	57.9	46.3	38.6	33.1	28.9	25.7	23.1	21.0	19.3	17.8	16.5	15.4	14.5	13.6	12.9	12.2	11.6
	VC	2.1	40	0.90	66.8	53.5	44.6	38.2	33.4	29.7	26.7	24.3	22.3	20.6	19.1	17.8	16.7	15.7	14.9	14.1	13.4
	VC	3.0	50	1.01	74.7	59.8	49.8	42.7	37.4	33.2	29.9	27.2	24.9	23.0	21.3	19.9	18.7	17.6	16.6	15.7	14.9
	C	4.0	60	1.10	81.8	65.5	54.6	46.8	40.9	36.4	32.7	29.8	27.3	25.2	23.4	21.8	20.5	19.3	18.2	17.2	16.4
	C	5.1	70	1.19	88.4	70.7	58.9	50.5	44.2	39.3	35.4	32.1	29.5	27.2	25.3	23.6	22.1	20.8	19.6	18.6	17.7
	M	6.1	80	1.27	94.5	75.6	63.0	54.0	47.3	42.0	37.8	34.4	31.5	29.1	27.0	25.2	23.6	22.2	21.0	19.9	18.9
	M	7.1	90	1.35	100.2	80.2	66.8	57.3	50.1	44.6	40.1	36.5	33.4	30.8	28.6	26.7	25.1	23.6	22.3	21.1	20.0
AMDF10	XC	0.3	15	0.61	45.5	36.4	30.3	26.0	22.7	20.2	18.2	16.5	15.2	14.0	13.0	12.1	11.4	10.7	10.1	9.6	9.1
	XC	0.6	20	0.71	52.5	42.0	35.0	30.0	26.3	23.3	21.0	19.1	17.5	16.2	15.0	14.0	13.1	12.4	11.7	11.1	10.5
	VC	1.2	30	0.87	64.3	51.4	42.9	36.7	32.2	28.6	25.7	23.4	21.4	19.8	18.4	17.1	16.1	15.1	14.3	13.5	12.9
	VC	2.1	40	1.00	74.3	59.4	49.5	42.4	37.1	33.0	29.7	27.0	24.8	22.8	21.2	19.8	18.6	17.5	16.5	15.6	14.9
	VC	3.0	50	1.12	83.0	66.4	55.3	47.4	41.5	36.9	33.2	30.2	27.7	25.5	23.7	22.1	20.8	19.5	18.4	17.5	16.6
	C	4.0	60	1.22	90.9	72.7	60.6	52.0	45.5	40.4	36.4	33.1	30.3	28.0	26.0	24.2	22.7	21.4	20.2	19.1	18.2
	C	5.1	70	1.32	98.2	78.6	65.5	56.1	49.1	43.7	39.3	35.7	32.7	30.2	28.1	26.2	24.6	23.1	21.8	20.7	19.6
	C	6.0	80	1.41	105.0	84.0	70.0	60.0	52.5	46.7	42.0	38.2	35.0	32.3	30.0	28.0	26.3	24.7	23.3	22.1	21.0
	M	7.0	90	1.50	111.4	89.1	74.3	63.6	55.7	49.5	44.6	40.5	37.1	34.3	31.8	29.7	27.8	26.2	24.8	23.4	22.3
AMDF11	XC	0.3	15	0.67	50.0	40.0	33.3	28.6	25.0	22.2	20.0	18.2	16.7	15.4	14.3	13.3	12.5	11.8	11.1	10.5	10.0
	XC	0.6	20	0.78	57.8	46.2	38.5	33.0	28.9	25.7	23.1	21.0	19.3	17.8	16.5	15.4	14.4	13.6	12.8	12.2	11.6
	VC	1.1	30	0.95	70.7	56.6	47.2	40.4	35.4	31.4	28.3	25.7	23.6	21.8	20.2	18.9	17.7	16.6	15.7	14.9	14.1
	VC	1.9	40	1.10	81.7	65.3	54.5	46.7	40.8	36.3	32.7	29.7	27.2	25.1	23.3	21.8	20.4	19.2	18.2	17.2	16.3
	VC	2.8	50	1.23	91.3	73.1	60.9	52.2	45.7	40.6	36.5	33.2	30.4	28.1	26.1	24.4	22.8	21.5	20.3	19.2	18.3
	C	3.8	60	1.35	100.0	80.0	66.7	57.2	50.0	44.5	40.0	36.4	33.3	30.8	28.6	26.7	25.0	23.5	22.2	21.1	20.0
	C	4.8	70	1.46	108.0	86.4	72.0	61.7	54.0	48.0	43.2	39.3	36.0	33.2	30.9	28.8	27.0	25.4	24.0	22.7	21.6
	C	5.7	80	1.56	115.5	92.4	77.0	66.0	57.8	51.3	46.2	42.0	38.5	35.5	33.0	30.8	28.9	27.2	25.7	24.3	23.1
	M	6.7	90	1.65	122.5	98.0	81.7	70.0	61.3	54.5	49.0	44.6	40.8	37.7	35.0	32.7	30.6	28.8	27.2	25.8	24.5
AMDF12	XC	0.3	15	0.73	54.6	43.6	36.4	31.2	27.3	24.2	21.8	19.8	18.2	16.8	15.6	14.5	13.6	12.8	12.1	11.5	10.9
	XC	0.6	20	0.85	63.0	50.4	42.0	36.0	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.8	14.8	14.0	13.3	12.6
	VC	1.1	30	1.04	77.2	61.7	51.4	44.1	38.6	34.3	30.9	28.1	25.7	23.7	22.0	20.6	19.3	18.2	17.1	16.2	15.4
	VC	1.9	40	1.20	89.1	71.3	59.4	50.9	44.6	39.6	35.6	32.4	29.7	27.4	25.5	23.8	22.3	21.0	19.8	18.8	17.8
	VC	2.7	50	1.34	99.6	79.7	66.4	56.9	49.8	44.3	39.8	36.2	33.2	30.7	28.5	26.6	24.9	23.4	22.1	21.0	19.9
	C	3.6	60	1.47	109.1	87.3	72.7	62.4	54.6	48.5	43.6	39.7	36.4	33.6	31.2	29.1	27.3	25.7	24.2	23.0	21.8
	C	4.5	70	1.59	117.9	94.3	78.6	67.4	58.9	52.4	47.1	42.9	39.3	36.3	33.7	31.4	29.5	27.7	26.2	24.8	23.6
	C	5.4	80	1.70	126.0	100.8	84.0	72.0	63.0	56.0	50.4	45.8	42.0	38.8	36.0	33.6	31.5	29.6	28.0	26.5	25.2
	M	6.4	90	1.80	133.7	106.9	89.1	76.4	66.8	59.4	53.5	48.6	44.6	41.1	38.2	35.6	33.4	31.4	29.7	28.1	26.7

Droplet data based off of ASABE S572.3 testing and Drift % is percent of <141um driftable fines.